



ARCHITECTURAL SERIES

NEW EVEREST & WINTER GRAY

Ideal for a multitude of building projects, Architectural Series' through-the-body colors and smooth or velour texture are a perfect choice for design versatility. Available in sizes ranging from Modular to Metric Jumbo and Utility, the Architectural Series is a product that scales easily to suit the project at hand, and can be paired well with other brick and stone products such as Vivace, Artiste, Finesse or Profile.



NEW! EVEREST

AVAILABLE SIZES:

Metric Modular, Modular, Premier Plus, Metric Norman, Metric Jumbo, Closure, Utility



NEW! WINTER GRAY

AVAILABLE SIZES:

Metric Modular, Modular, Premier Plus, Metric Norman, Metric Jumbo, Closure, Utility

ARCHITECTURAL SERIES

SIZES



Metric Modular
 Length 190 mm (7 1/2")
 Height 57 mm (2 1/4")
 Depth 90 mm (3 1/2")
 Bricks per square foot 7
 Bricks per square meter 75



Modular
 Length 194 mm (7 5/8")
 Height 57 mm (2 1/4")
 Depth 92 mm (3 5/8")
 Bricks per square foot 6.8
 Bricks per square meter 73.5



Premier Plus
 Length 257 mm (10 1/8")
 Height 79 mm (3 1/8")
 Depth 90 mm (3 1/2")
 Bricks per square foot 3.9
 Bricks per square meter 42



Metric Norman
 Length 290 mm (11 1/2")
 Height 57 mm (2 1/4")
 Depth 90 mm (3 1/2")
 Bricks per square foot 4.6
 Bricks per square meter 49.8



Metric Jumbo
 Length 290 mm (11 1/2")
 Height 90 mm (3 1/2")
 Depth 90 mm (3 1/2")
 Bricks per square foot 3
 Bricks per square meter 33



Closure
 Length 194 mm (7 5/8")
 Height 92 mm (3 5/8")
 Depth 92 mm (3 5/8")
 Bricks per square foot 4.5
 Bricks per square meter 48.4



Utility
 Length 295 mm (11 5/8")
 Height 92 mm (3 5/8")
 Depth 92 mm (3 5/8")
 Bricks per square foot 3
 Bricks per square meter 32.3

COLORS



SPECIFICATIONS

Manufactured in our Farmersburg, Indiana Plant

Product Property	CSA	ASTM	Typical Brampton Brick Range*
Compressive Strength (min)	> 21 MPa	> 3000 psi	40 – 60 MPa or 5800 – 8700 psi
24 hour cold water absorption			3% - 6%
5 hour boil water absorption	< 17%	< 17%	4% - 8%
C/B Ratio	< 0.78	< 0.78	0.65 - 0.75
Based on CSA A82 for Exterior Grade (EG) brick, Type X and ASTM C216 for Severe Weather (SW) Brick, Type FBX			*not applicable if 24 hr CWA <8%

Minimum orders apply. Check with a Brampton Brick Sales Representative on product availability prior to specifying. For additional information, please visit our website at BramptonBrick.com

To find a dealer nearest you please visit:

BramptonBrick.com

Or, call us toll free at:

1.800.GO.BRICK (462-7425) (Canada)

1.844.GO.BRICK (462-7425) (USA)

Product representations shown in this publication are intended to convey the general color, texture and appearance of the product. Variations may occur in the manufacturing and printing process. Always select from an actual product sample.